

Fig. 5953 & 5953G Semi-lugged Metrex Commissioning Sets



FEATURES & BENEFITS


- Robust iron body materials for long service life
- Precise flow regulation and accurate measurement
- Semi-lugged – easy to install and operate
- Positive flow control at all settings



MATERIAL SPECIFICATION

Component	Material	Specification		
		BS EN	ASTM	DIN
Valve	Figure 953G (see 953G for materials)	-	-	-
Test Points	Figure 631	-	-	-
Extension Sleeve	Gunmetal	1400LG2	B62	1705 G-CuSn5ZnPb
Housing	Cast Iron (Nickel Plated)	1452 Gr220	A126 Cl B	1691 GG22
Orifice Plate	Stainless Steel	970 316S31	AISI 316	17440 X5CrNiMo1812

DIMENSIONAL DRAWINGS



DIMENSIONS & WEIGHTS

Nom Size	mm	50	65	80	100	125	150	200	250	300
A	mm	133	151	166	192	221	246	300	358	418
B	mm	135	145	160	165	180	190	225	255	275
Weight	kg	10.0	10.8	11.0	13.0	16.0	18.5	29.8	40.0	53.0

PRESSURE/TEMPERATURE RATING

EPDM Seat
16 bar from -10 to 120°C

SERVICE RATING

Suitable for Chilled Water, LTHW and MTHW

TEST PRESSURES

Shell: 24 bar
Seat: 17.6 bar

SPECIFICATION

A close coupled commissioning set comprising a lugged butterfly valve and metering station to offer all the advantages of the close coupled concept together with an accuracy of ±5% of flow rate.

Gear operation provides infinitely variable settings between fully open and closed positions.


The commissioning set is supplied as a single unit.

Supplied complete with Figure 631 test points and necessary bolting for connection of the valve end to the system.

Comprehensive flow charts available.

NOTE

The valve should be not less than 30° open for regulation duties. Lever operated version available in sizes 50 to 200mm.



For commissioning valve coefficients (Kv) please refer to relevant section in this brochure. (See Index)

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Hattersley Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.